



Features

- Different Lighting design
- Anti-glare
- External power supply

Applications

- Hotels and other residential buildings
- Luxurious (franchised) store, museum, auditoria, shops

Part No.	Artemi Downlight LD006
Article number	CT 60031
Fixture colour	White
Wattage (W)	9
Dimmable	No
Lumens (lm)	450
CRI (Ra)	80
CCT (K)	3000
Beam Angle (deg)	140
Cut size (mm)	120
Energy efficiency class	A
PF	0.95
Voltage (V)	AC 176-264V
Frequency (Hz)	50/60
Current (mA)	
Socket	Wire
Switching Cycles	100.000
Lifespan (hrs)	40.000
Working Temperature (°C)	-20 ~ 40
Storage Temperature (°C)	-20 ~ 60
Weight (g)	
EAN code	

* Note: Data is subject to change without prior notice. Please visit www.civilight.nl for further information.

Cautions

- Power off before replacement
- Don't touch the lamp when lighting

CIVILIGHT LIGHTING CO., LTD

Address 5/F, Building D, HongFa Hi-Tech Park, Shiyan, Shenzhen, China W: www.cvitec.info

VEZALUX B.V.

Wernhoutseweg 38A, 4884 AW, Wernhout, The Netherlands

Tel: +31 (0)76 5971220, Fax: +31 (0)76-5976841 E: info@vezalux.nl W: www.civilight.nl