



Features

- Different Lighting design
- Anti-glare
- External power supply

Applications

- Hotels and other residential buildings
- Luxurious (franchised) store, museum, auditoria, shops

Part No.	Artemi Downlight LD006 D2W
Article number	CT 60054
Fixture colour	White
Wattage (W)	18
Dimmable	Yes
Lumens (lm)	850
CRI (Ra)	90
CCT (K)	4000-3000
Beam Angle (deg)	140
Cut size (mm)	170
Energy efficiency class	A
PF	0.95
Voltage (V)	AC 176-264V
Frequency (Hz)	50/60
Current (mA)	
Socket	Wire
Switching Cycles	100.000
Lifespan (hrs)	40.000
Working Temperature (°C)	-20 ~ 40
Storage Temperature (°C)	-20 ~ 60
Weight (g)	
EAN code	

* Note: Data is subject to change without prior notice. Please visit www.civilight.nl for further information.

Cautions

- Power off before replacement
- Don't touch the lamp when lighting

CIVILIGHT LIGHTING CO., LTD

Address 5/F, Building D, HongFa Hi-Tech Park, Shiyan, Shenzhen, China W: www.cvitec.info

VEZALUX B.V.

Wernhoutseweg 38A, 4884 AW, Wernhout, The Netherlands

Tel: +31 (0)76 5971220, Fax: +31 (0)76-5976841 E: info@vezalux.nl W: www.civilight.nl