


DOWNLIGHT LD013 9W 4000K 160°



Features

- Die casting aluminum body good heat dissipation
- Special coating with high terminal conductivity & radiation materials
- External power supply (dimnable and non-dimnable)

Applications

- Hotels and other residential buildings
- Luxurious (franchised) store, museum, auditoria, shops

Part No.	LD013 9 840 CVL 139840
Article number	CVL 139840
Fixture colour	White
Wattage (W)	9
Dimmable	Optional
Lumens (lm)	665
CRI (Ra)	>80
CCT (K)	4000
Beam Angle (deg)	160
Cut size (mm)	105
Energy efficiency class	A
PF	0.95
Voltage (V)	AC 220-240V
Frequency (Hz)	50/60
Current (mA)	400
Socket	Wire
Switching Cycles	100.000
Lifespan (hrs)	25.000
Working Temperature (°C)	-20 ~ 40
Storage Temperature (°C)	-20 ~ 60
Weight (g)	
EAN code	

* Note: Data is subject to change without prior notice. Please visit www.cvl-lighting.com for further information.

Cautions

- Power off before replacement
- Don't touch the lamp when lighting

CIVILIGHT LIGHTING CO., LTD

Address 5/F, Building D, HongFa Hi-Tech Park, Shiyan, Shenzhen, China W: www.cvl-lighting.com

VEZALUX B.V.

Wernhoutseweg 38A, 4884 AW, Wernhout, The Netherlands

Tel: +31 (0)76 5971220, Fax: +31 (0)76-5976841 E: info@vezalux.nl W: www.civilight.nl