

9W HALED III DMR16 621LM Dimmable

CIVILIGHT




Features

- Flicker-free light
- 99% of halogen lighting effect
- HALED optical design
- Smooth dimming
- Glare-free
- Switching power supply
- CE and RoHS2 compliant

Applications

- Spotlighting for accents
- Display and shop windows
- Home, museum, hotel, theater,
- Bar, café and other indoor light

Article number	CL 2529
Halogen Equivalent (W)	55
Wattage (W)	9
Dimmable	Yes
Lumens (lm)	621
CRI(Ra)	80
CCT (K)	3000
Beam Angle (deg)	36
Luminous Intensity (cd)	1500
Energy efficiency class	A
PF	0.9
Voltage (V)	AC 12V
Frequency (Hz)	50/60
Current (mA)	850
Socket	GU5.3
Switching Cycles	100000
Lifespan (hrs)	25000
Working Temperature (°C)	-20 ~ 40
Storage Temperature (°C)	-20 ~ 60
Weight (g)	53
EAN code	6901029025293



* Note: Data is subject to change without prior notice. Please visit www.civilight.com for further information.

Cautions

- Power off before replacement
- Don't touch the lamp when lighting
- Don't use it in sealed fixture
- Indoor use

CIVILIGHT LIGHTING CO., LTD

Address 5/F, Building D, HongFa Hi-Tech Park, Shiyan, Shenzhen, China W: www.civilight.com

VEZALUX B.V.

Wernhoutseweg 38A, 4884 AW, Wernhout, The Netherlands

Tel: +31 (0)76 5971220, Fax: +31 (0)76-5976841 E: info@vezalux.nl W: www.civilight.nl